



I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on 7/14/04

Patty Wilson
Patty Wilson
Date of Signature 7/14/04

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Palazoglu

Group Art Unit: 2859

Serial No.: 10/767,427

Examiner: To be Assigned

Filed: January 28, 2004

Docket No.: 297/164/2

Confirmation No.: 7231

For: METHODS, SYSTEMS, AND DEVICES FOR EVALUATION OF THERMAL TREATMENT

PRELIMINARY AMENDMENT

Mail Stop Patent Application
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Please amend the application as follows:

IN THE DESCRIPTION OF THE DRAWINGS:

Please replace the "Brief Description of the Drawings" with the following:

Brief Description of the Drawings

Exemplary embodiments of the subject matter will now be explained with reference to the accompanying drawings, of which:

Figure 1 is a schematic diagram of combining a first and second magnet at opposing magnetic poles to achieve a combined magnet;

Figure 2 is a schematic diagram of the result of combining a first and second magnet at similar magnetic poles to achieve a combined magnet;

Figures 3A, 3C, and 3E are schematic diagrams of a magnetically detectable particle in a state below a predetermined conservative temperature;

Figure 3B, 3D, and 3F are schematic diagrams of the magnetically detectable particle of Figure 3A, 3C, and 3E, respectively, in a state above a predetermined conservative temperature;

Figures 3G-3I are schematic diagrams of the assembly and operation of one embodiment of a magnetically detectable particle comprising multiple magnets;

Figures 3J-3L are schematic diagrams of carrier particles comprising multiple detectable particles;

Figure 4 is a schematic diagram of the principle of forced coupling and fixing similar magnets;

Figure 5A is a schematic diagram of another embodiment of a magnetically detectable particle in a state below a predetermined conservative temperature;

Figure 5B is a schematic diagram of the magnetically detectable particle of Figure 5A in a state above the predetermined conservative temperature;

Figure 6A is a schematic diagram of another embodiment of a magnetically detectable particle in a state below a predetermined conservative temperature;

Figure 6B is a schematic diagram of the magnetically detectable particle of Figure 6A in a state above the predetermined conservative temperature;

Figure 6C is a schematic diagram of another embodiment of a magnetically detectable particle in a state below a predetermined conservative temperature;

Figures 6D and 6E are schematic diagrams of the magnetically detectable particle of Figure 6C in a state above the predetermined conservative temperature;

Figure 6F is a schematic diagram of a carrier particle comprising a detectable particle comprising more than two magnets (e.g. three magnets), all assembled using the same adhesive;

Figure 7A is a schematic diagram of another embodiment of a magnetically detectable particle in a state below a first predetermined conservative temperature;

Figure 7B is a schematic diagram of the magnetically detectable particle of Figure 7A in a state above the first predetermined conservative temperature and below a second predetermined temperature;

Figure 7C is a schematic diagram of the magnetically detectable particle of Figures 7A and 7B in a state above the first and second predetermined temperatures;

Figures 7D-7G are schematic diagrams of carrier particles comprising multiple detectable particles;

Figure 8A is a schematic diagram of another embodiment of a magnetically detectable particle in a state below a predetermined conservative temperature;

Figure 8B is a schematic diagram of the magnetically detectable particle of Figure 8A in a state above the predetermined conservative temperature;

Figure 9 is an experimental system for use in demonstrating magnetically detectable particles, carrier particles, and related devices;

Figure 10 is a ~~still-image~~ perspective view of a simulated particle containing a coupled magnet sensor/detector;

Figure 11 is a ~~still-image~~ perspective view of another simulated particle including a thermocouple lead having contact with a magnet assembly;

Figure 12 is a ~~still-image~~ perspective view of a simulated particle with the experimental system of Figure 9;

Figure 13 is a ~~still-image~~ perspective view of a data acquisition system including a display for presenting acquired temperature information and magnetic field strength data;

Figures 14A-14D are different ~~still-image~~ perspective views of a triple magnet assembly being assembled in a simulated particle;

Figure 15 is still image of a magnet pair with a U.S. penny for providing a size scale perspective;

Figure 16 is a graph of magnetic field strength from two naturally aligned identical magnets with no heating;

Figure 17 is a graph of magnetic field strength from two aligned and attached magnets with no heating;

Figure 18 is a graph of magnetic field strength from two aligned and attached with heating;

Figure 19 is a graph showing applied temperature versus magnetic field strength;

Figure 20 is a graph showing applied temperature versus magnetic field strength;

Figure 21 is a graph showing applied temperature versus magnetic field strength;

Figures 22 is a graph showing applied temperature versus magnetic field strength;

Figures 23-27 are different graphs of experimental results obtained by testing the device shown in Figures 3A and 3B with an adhesive comprising a metal alloy with a melting point of 138.3°C;

Figures 28-30 are different graphs of experimental results obtained by testing the device shown in Figures 3A and 3B with an adhesive comprising a metal alloy with a melting point of 123.9°C;

Figure 31 is a graph of magnetic field strength versus temperature obtained using the assembly shown in Figures 5A and 5B was tested using the experimental system shown in Figure 9;

Figure 32 is a graph of magnetic field strength versus temperature obtained using the assembly shown in Figures 6A and 6B was tested using the experimental system shown in Figure 9;

Figure 33 is a graph of magnetic field strength versus temperature obtained using the assembly shown in Figure 7 was tested using the experimental system shown in Figure 9;

Figure 34 is a schematic diagram of an exemplary system for conservative evaluation, validation, and monitoring of thermal processing;

Figure 35 is a schematic diagram of a computer system that can facilitate the design of a carrier particle about matching the conservative behavior characteristics of a selected target particle;

Figure 36 is a flow chart that illustrates a process for providing a carrier particle having materials and dimensions to provide characteristics for the carrier particle that about match the conservative behavior characteristics of a selected target particle;

Figure 37 ~~are~~ is an illustration of two screen displays show results indicating that using an overly conservative carrier particle design can result in a potato food particle receiving cumulative lethality in its cold spot up to two orders of magnitude greater than required for commercial sterility;

Figure 38 ~~are~~ is an illustration of two screen displays that show other simulations applied to a carrier particle design and 3/8 inch potato food particle, respectively, under similar conditions;

Figure 39 ~~are~~ is an illustration of two screen displays that show other simulations applied to a carrier particle design and a 0.5 inch x 0.5 inch, cylindrical, potato food particle, respectively, under similar conditions;

Figure 40 ~~are~~ is an illustration of two screen displays that show other simulations applied to a carrier particle design and a 3/8 inch x 3/8 inch, cylindrical, potato food particle, respectively, under similar conditions;

Figure 41 is a schematic diagram of a 0.5 inch, cubic particle design for simulation by a spatial simulation engine;

Figure 42 is an illustration of a screen display showing exemplary simulation results for cubic particle design of Figure 41;

Figure 43 is schematic diagram showing a grid relating to Figure 42 of the result of heating each of its cubes in the thermal processing simulation;

Figure 44 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch TPX carrier particle design;

Figure 45 is a schematic diagram showing a grid of the result of heating the TPX carrier particle design of Figure 44 in the same thermal processing simulation of the target particle;

Figure 46 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch nylon carrier particle design;

Figure 47 is a schematic diagram showing a grid of the result of heating the nylon carrier particle design of Figure 46 in the same thermal processing simulation of the target particle;

Figure 48 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch TEFLON™ carrier particle design;

Figure 49 is a schematic diagram showing a grid of the result of heating the TEFLON™ carrier particle design of Figure 44 in the same thermal processing simulation of the target particle;

Figure 50 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch polypropylene carrier particle design;

Figure 51 is a schematic diagram showing a grid of the result of heating the polypropylene carrier particle design of Figure 50 in the same thermal processing simulation of the target particle;

Figure 52 is a schematic diagram of a 3/8 inch cubic particle design for simulation by spatial simulation engine;

Figure 53 is an illustration of a screen display showing exemplary simulation results for the cubic particle design shown in Figure 52;

Figure 54 is a schematic diagram showing a grid of the result of heating each of cubes in the thermal processing simulation;

Figure 55 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch TPX carrier particle design;

Figure 56 is a schematic diagram showing a grid of the result of heating each of cubes in the thermal processing simulation;

Figure 57 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch nylon carrier particle design;

Figure 58 is a schematic diagram showing a grid of the result of heating the nylon carrier particle design of Figure 57 in the same thermal processing simulation of the target particle;

Figure 59 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch TEFLON™ carrier particle design;

Figure 60 is a schematic diagram showing a grid of the result of heating the TEFLON™ carrier particle design of Figure 59 in the same thermal processing simulation of the target particle;

Figure 61 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch polypropylene carrier particle design;

Figure 62 is a schematic diagram showing a grid of the result of heating the polypropylene carrier particle design of Figure 61 in the same thermal processing simulation of the target particle;

Figure 63 is a schematic diagram of a cylindrical particle design for simulation by spatial simulation engine;

Figure 64 is an illustration of a screen display showing exemplary simulation results for the cylindrical particle design shown in Figure 63;

Figure 65 is a schematic diagram showing a plurality of circular portions and the result of heating each of circular portions in the thermal processing simulation;

Figure 66 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch, TPX carrier particle design;

Figure 67 is a schematic diagram showing a plurality of circular portions of the result of heating the TPX carrier particle design of Figure 66 in the same thermal processing simulation of the target particle;

Figure 68 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch nylon carrier particle design;

Figure 69 is a schematic diagram showing a plurality of circular portions of the result of heating the nylon carrier particle design of Figure 46 in the same thermal processing simulation of the target particle;

Figure 70 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch TEFLON™ carrier particle design;

Figure 71 is a schematic diagram showing a plurality of circular portions of the result of heating the TEFLON™ carrier particle design of Figure 66 in the same thermal processing simulation of the target particle;

Figure 72 is an illustration of a screen display showing exemplary simulation results for a 0.5 inch polypropylene carrier particle design;

Figure 73 is a schematic diagram showing a plurality of circular portions of the result of heating the polypropylene carrier particle design of Figure 72 in the same thermal processing simulation of the target particle;

Figure 74 is a schematic diagram of a cylindrical particle design for simulation by a spatial simulation engine;

Figure 75 is an illustration of a screen display showing exemplary simulation results for the cylindrical particle design shown in Figure 74;

Figure 76 is a schematic diagram showing a plurality of circular portions of the result of heating each of circular portions in the thermal processing simulation;

Figure 77 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch TPX carrier particle design;

Figure 78 is a schematic diagram showing a plurality of circular portions of the result of heating the TPX carrier particle design of Figure 77 in the same thermal processing simulation of the target particle;

Figure 79 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch nylon carrier particle design;

Figure 80 is a schematic diagram showing a plurality of circular portions of the result of heating the nylon carrier particle design of Figure 57 in the same thermal processing simulation of the target particle;

Figure 81 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch TEFLON™ carrier particle design;

Figure 82 is a schematic diagram showing a grid of the result of heating the TEFLON™ carrier particle design of Figure 81 in the same thermal processing simulation of the target particle;

Figure 83 is an illustration of a screen display showing exemplary simulation results for a 3/8 inch polypropylene carrier particle design;

Figure 84 is a schematic diagram showing a grid of the result of heating the polypropylene carrier particle design of Figure 83 in the same thermal processing simulation of the target particle;

Figure 85 is a flow chart that illustrates a process for designing a carrier particle having characteristics about matching the conservative behavior characteristics of a selected target particle;

Figure 86 is an illustration of a screen display of an application providing a dropdown menu for selecting a target food particle for simulation;

Figure 87 is an illustration of a screen display of an application providing a menu for receiving operator input for designing a carrier particle;

Figures 88A and 88B are illustrations of screen displays of an application providing the results of the information entered in the screen display of Figure 87;

Figures 89A and 89B are illustrations of screen displays of an application providing exemplary results of simulation information entered by an operator; and

Figures 90A and 90B are illustrations of screen displays of an application providing exemplary results of other simulation information entered by an operator.